

Cod. Articolo 43.8683

TS-253B-4G - TS-253B-4G - 4713213510995 - QNAP

NAS QNAP TS-253B-4G 2HD 3,5"/2,5";
SATA6G>NO HD<2P GIGA 10G-READY-5P
USB3.0-4GB DDR3L-QUADCORE INTEL CEL.APOLLO
LAKE J3455 1.5GHZ



Ordering P/N
TS-253B-4G

CPU:
Intel® Celeron® J3455 quad-core 1.5 GHz, up to 2.3 GHz

Encryption Acceleration:
Si (AES-NI)

Graphics:
Intel® HD Graphics 500

System memory:
8GB DDR3L
(2 x 4GB)

Maximum Memory:
8GB

Total Memory Slots:
2 x DDR3L SODIMM slots
(For dual-DIMM configuration, you must use a pair of identical DDR3L modules.)

Drive:
Hot-swappable 2 x 3.5"/2.5" SATA 6Gb/s HDD/SSD

GbE LAN Port:
2 x RJ45 Gigabit LAN port

10GbE LAN Port:
Optional 10 Gigabit LAN port via a PCIe expansion card

USB 3.0 Port:
5 x USB 3.0 Type-A ports

USB QuickAccess:
USB Type-C

PCIe Slot:
1 PCIe 2.0 x2 slot

HDMI Port:
2 x HDMI v1.4b, up to 3840 x 2160, 30 Hz

Audio Input:
2 x 3.5mm microphone input jacks

Audio Output:
speaker, 3.5mm line out jack

Display:
0.96" monochrome OLED

LED Indicators:
Status/Power, LAN, USB, Drives, SD card, USB QuickAccess

Buttons:
Power, USB copy, Reset, Capacitive touch buttons (select, enter)

Infrared Receiver:
Si supplied with a QNAP RM-IR004 remote control (compatible with RM-IR002 remote control)

SDXC Card Reader:
Si

Other Interfaces:
Kensington security slot

Dimension (HxWxD):
168 x 105 x 226 mm

Weight:
1.66 kg

Sound Level*:
Operating low speed: 16.7 dB(A)

Operating Temperature:
0 ~ 40°C (32~73°F ~ 104~73°F)

Relative Humidity:
5~95% RH non-condensing, wet bulb: 27~73°C (80.6~73°F)

Power Consumption:
HDD sleep: 13.07W

Typical Operation:
20.42W

Power Supply:
65W AC adapter, 100-240V

Fan:
1 x 7 cm

Package Contents:
NAS, QIG, 2 x RJ45 ethernet cables, AC adapter, power cord, 2.5" drive screw kit, RM-IR004 remote control