

Cod. Articolo 42.9043
A03-S100 - 8026974008950 - ATLANTIS

UPS ATLANTIS A03-S100 800VA/400W
ONEPOWER-DISP.LCD-LINE INTERACTIVE-AVR-PORTA
USB-BATT.12V 7AH-1XIEC+1XSCHUKO-GAR.2 ANNI



Power Rating (VA)
800

Power Rating (W)
400

Input
Voltage: 160-290V
Frequency: 50Hz \pm 5%

Output
Voltage: 190-245 [AC/AVR] / 220V(\pm 7%) [Battery]
Frequency: 50Hz (\pm 1%)
AVR: Built-in
Waveform: Simulated SineWave

Transfer Line/Battery
Less than 4ms (typical)

Efficiency Battery
Total Efficiency Over 80%
Voltage: 12VDC
Capacity: 12V/7.2A
Quantity: 1
Recharge Time: 6-8 hours to (90%)
Type: Sealed Maintenance Free Lead Acid VRLA Type

Indicators
LCD: Utility Normal, Backup, Battery Load, Battery Voltage, Input Voltage, Output Voltage, Load, AVR and Battery/Fault conditions

Protection
- Overload AC Buzzer continuously alarms
- Overload Inverter Buzzer continuously alarms
- Short Circuit INV Input Fuse & Electric Circuit
- Short Circuit AC Electric Circuit
- Battery Over-drain Two stages: Controlled Battery Low Warning & Cut Off
- Spike Suppression: Meets EN61000-4-5
- Noise Suppression: Meets EN50991-1

Connections
Output: 1 x IEC + 1 Schuko (Battery Power Supplied)
Computer: USB (USB Cable isn't included)

Backup Time
10 to 30 mins for typical PC Load

Mechanical
Dimensions (WxHxD): 100 x 140 x 292 mm
Net Weight (with Battery): 4.2 Kg

Environments
Temperature: 0-40° C
Humidity: 0-95% (non-condensing)

Certification
CE