



Cod. Articolo 42.932
A03-P841 - 8026974006468 - ATLANTIS

UPS ATLANTIS A03-P841 1100VA/550W SERVER LINE
INTERACTIVE - AVR - INTERF.USB. UPSILON 2000 INCL.
-GARANZIA 2 ANNI

Power Rating (VA)
1100

Power Rating (W)
550

Input
Voltage: 162-268V
Frequency: 50Hz \pm 5%

Output
Voltage: 220V(\pm 10%) [AC] / 220V(\pm 10%) [INV]
Frequency: 50Hz (\pm 1%)
Waveform: Simulated SineWave

Transfer Line/Battery
Less than 2-6 ms (typical)

Efficiency Battery
Total Efficiency Over 80%
Voltage: 12Vdc
Capacity: 12V/9.0A
Quantity: 1
Recharge Time: 4 hours to (90%)
Type: Sealed Maintenance Free Lead Acid VRLA Type

Indicators (1 Led)
- AC Mode (Green lighting)
- Battery mode (Green flashing every 10 seconds)
- Low Battery (Green flashing every seconds and)

Protection
Overload AC Buzzer sound every 0.5 seconds then UPS shuts down after 10 seconds (>110%)
Overload Inverter UPS shuts down after 10 seconds (>110%)
Short Circuit INV Input Fuse & Electric Circuit
Short Circuit AC Electric Circuit
Battery Over-drain Two stages: Controlled Battery Low Warning & Cut Off
Modem RJ11
Spike Suppression: Meets EN61000-4-5
Noise Suppression: Meets EN50991-1

Alarm
• Battery Mode (sound every 10 seconds)
• Low Battery (sound every seconds)
• OverLoad (sound every 0.5 seconds)
• Fault (continuously sounding)

Connections
Output: 4 x IEC (Battery Power Supplied)
Computer: USB (USB Cable isn't included)

Backup Time

10 to 30 mins for typical PC Load

Mechanical

Dimensions (WxHxD): 101 x 142 x 280 mm

Net Weight(with Battery): 5 Kg

Environments

Temperature: 0-40° C

Humidity: 0-95% (non-condensing)

Certification

CE

SW

- Supports Windows® 2000/2003/2008, XP/Vista and Windows® 7/8
- Support Mac OS 10.5/10.6/10.7
- Linux: Redhat 8,9, Fedora 5, RedHat Enterprise AS3, AS5, AS6 (32bit), SUSE 10 (32bit), Ubuntu 8.X, 9.X, 10.X(32bit), OpenSUSE 11.2 (32bit), Debian 5.x, 6x (32bit)
- Linux: RedHat Enterprise AS6 (64bit), SUSE 10 (64bit), Ubuntu 10.X(64bit), OpenSUSE 11.2 (64bit), Debian 6x (64bit)