

Cod. Articolo 42.921  
A03-HP701 - 8026974006420 - ATLANTIS

UPS ATLANTIS A03-HP701 700VA/360W SINEWAVE  
UPS+STABILIZ+FILTRI SW DI CONTROLLO INCLUSO -  
GARANZIA 2 ANNI-



Power Rating(VA)  
700  
Power Rating(W)  
360  
INPUT  
Voltage: 165-275V  
Frequency: 50Hz±5%  
OUTPUT  
Voltage: 220V(±10%) [AC] / 220V(±7%) [INV]  
Frequency: 50Hz (±1%)  
AVR Built-in  
Waveform True SineWave  
TRANSFER  
Less than 2-6 ms (typical),  
Line/Battery  
10 Max  
EFFICIENCY  
Total Efficiency Over 80%  
BATTERY  
Voltage 12VDC  
Capacity 12V/7.2Ah  
Quantity 1  
Recharge Time  
6-8 hours to (90%)  
Type Sealed Maintenance Free Lead Acid VRLA Type  
INDICATORS (LCD Display)  
Input Voltage, Output Voltage, Load Level Indicator, Overload, Utility  
Normal, Backup, Battery Low and Battery Fault conditions  
PROTECTION  
Overload AC Buzzer continuously alarms then UPS shuts down after  
10 seconds (>110%)  
Overload Inverter UPS shuts down after 10 seconds (>110%)  
Short Circuit INV Input Fuse & Electric Circuit  
Short Circuit AC Electric Circuit  
Battery Over-drain Two stages: Controlled Battery Low Warning &  
Cut Off  
Modem RJ11  
Spike Suppression Meets EN61000-4-5  
Noise Suppression Meets EN50991-1  
ALARM  
Battery Mode (sound every 10 seconds)  
Low Battery (sound every seconds)  
OverLoad (sound every 0.5 seconds)  
Battery Replacement Alarm (sound every 2seconds)  
Fault (continuously sounding)  
CONNECTIONS  
Output 3xIEC (Battery Power Supplied)  
Computer USB  
Backup Time  
10 to 30 mins for typical PC Load

#### MECHANICAL

Dimensions (WxHxD):

100 x 145 x 328 mm

Net Weight (with Battery): 6 Kg

#### ENVIRONMENTS

Temperature 0°-40° C

Humidity 0-95% (non-condensing)

Package Contents

- HostPower Line Interactive SineWave UPS
- 2 x IEC cables, 1x USB cable
- Fuse
- Manual (Italian, English and French)
- Warranty and WEEE Instructions

#### CERTIFICATION

CE